



Calore



Mansioni gravose

Resistenza superiore al calore con protezione completa di mano e polso

- Progettato per manipolazione intermittente di oggetti caldi fino a 180°C.
- Garantisce elevata resistenza a tagli, abrasioni e lesioni di minore entità.
- Migliora la presa sulle superfici asciutte e oleose.
- Comodo e flessibile: interno in feltro non tessuto per assorbire il sudore.



Industrie

- Industria automobilistica
- Chimica

Applicazioni


- Stampaggio su presse a iniezione
- Manipolare parti strutturali stampate
- Esecuzione di test
- Saldatura

Caratteristiche chiave

- Isolamento in feltro non tessuto e barriera termica su tutta la lunghezza, progettato per manipolazioni intermittenti di oggetti asciutti fino a 200°C/400°F
- La costruzione bicomponente elimina le cuciture esterne per migliorare comfort delle dita, destrezza e flessibilità
- Il rivestimento impregnato in nitrile protegge contro strappi, perforazioni, abrasioni e tagli
- Offre una presa eccellente nella manipolazione di superfici asciutte o oleose
- Confortevole e flessibile: fodera in feltro non tessuto che assorbe il sudore
- Non contiene amianto
- Conforme ai requisiti FDA di manipolazione degli alimenti

Standard riguardanti le prestazioni & Conformità normativa

Conforme a REACH



Specifiche

MARCHIO MODELLO	DESCRIZIONE	Numero di aghi	TAGLIA	LUNGHEZZA	CONFEZIONAMENTO
ActivArm® 42-474	Materiale della fodera: Poliestere non tessuto, Cotone poliestere Modello di polso: Polso lungo	N/A	9, 10	343-356 mm; 13.5-14 inches	• 12 paia per sacchetto; 6 sacchetti per cartone

Per maggiori informazioni, visitate il nostro sito www.ansell.com, oppure chiamateci al numero

Europa, Medio Oriente ed Africa

Ansell Healthcare Europe NV
Riverside Business Park
Blvd International, 55
1070 Brussels, Belgium
T: +32 (0) 2 528 74 00
F: +32 (0) 2 528 74 01

North America Region

Ansell Healthcare Products LLC
111 Wood Avenue South,
Suite 210
Iselin, NJ 08830, USA
+1 800 800 0444
F: +1 800 800 0445

Australia

Ansell Limited
Level 3, 678 Victoria Street,
Richmond, Vic, 3121
Australia
T: +61 1800 337 041
F: +61 1800 803 578

Regioni dell'Asia Pacifico

Ansell Global Trading Center
(Malaysia) Sdn Bhd
Prima 6, Prima Avenue
Block 3512, Jalan Teknokrat 6
T: +603 8310 6688
F: +603 8310 6699

America Latina & Caraibi

Ansell Commercial Mexico S.A. de C.V.
Blvd. Bernardo Quintana No. 7001-C,
Q7001 Torre II,
Suites 1304, 1305 y 1306,
Col. Centro Sur, c.p. 76079
Queretaro, Qro. Mexico
T: +52 442 248 1544 / 248 3133

Canada

Ansell Canada
105 Lauder
Owensville, QC J2K 2K8
Canada
T: +1 800 363 8340
F: +1 800 267 3551

Ansell, ® e ™ sono marchi commerciali di proprietà di Ansell Limited o di una delle società affiliate. Brevettati negli USA e in attesa di brevetti negli USA e fuori dagli USA: www.ansell.com/patentmarking © 2020 Ansell Limited. Tutti i diritti riservati.

Né il presente documento, né eventuali altre dichiarazioni formulate da o per conto di Ansell devono essere interpretati come garanzia di commerciabilità o idoneità per un determinato utilizzo dei prodotti Ansell. Ansell non assume alcuna responsabilità riguardo a idoneità o adeguatezza nella scelta dei guanti per un uso specifico da parte dell'utente finale.



42-474

Flexible full-length heat barrier.



Heat



Heavy Duty

Superior heat resistance with complete protection for hand and wrist.

- Designed for intermittent handling of dry hot objects up to 200°C / 400°F
- Provides resistance to cuts and abrasion
- Enhances grip on dry and oily surfaces
- Comfortable & flexible: sweat absorbent nonwoven felt inner liner



Industries

- Automotive
- Chemical

Applications

- Press injection molding
- Handling molded structural parts
- Testing
- Welding

WWW.ANSELL.COM



42-474

Flexible full-length heat barrier.

Key Features

- Non-woven felt insulation and a full-length heat barrier designed for intermittent handling of dry objects up to 200°C / 400°F
- Two-piece construction eliminates outseams for better finger comfort, dexterity and flexibility
- Bonded nitrile coating protects against snags, punctures, abrasions and cuts
- Provides excellent grip when handling dry or oily surfaces
- Comfortable & flexible: sweat absorbent non-woven felt inner
- Contains no asbestos
- Compliant to FDA food handling requirements

Performance Standards & Regulatory Compliance

REACH Compliant

- 0493
- 2241B
- 2241
- X2XXXX

Specifications

BRAND STYLE	DESCRIPTION	Gauge	SIZE	LENGTH	PACKAGE
ActivArmr® 42-474	Liner Material: Non-Woven Polyester, Polycotton Cuff Style: Gauntlet	N/A	9, 10	343-356 mm; 13.5-14 inches	12 Pair Per Bag; 6 Bags Per Carton

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

- Ansell Healthcare Europe NV
Riverside Business Park
Blvd International, 55
1070 Brussels, Belgium
- T: +32 (0) 2 528 74 00
- F: +32 (0) 2 528 74 01

North America Region

- Ansell Healthcare Products LLC
111 Wood Avenue South,
Suite 210
Iselin, NJ 08830, USA
- T: +1 800 800 0444
- F: +1 800 800 0445

Australia

- Ansell Limited
Level 3,678 Victoria Street,
Richmond, Vic, 3121
Australia
- T: +61 1800 337 041
- F: +61 1800 803 578

Asia Pacific Region

- Ansell Global Trading Center
(Malaysia) Sdn Bhd

Prima 6, Prima Avenue

Block 3512, Jalan Teknokrat 6

- T: +603 8310 6688
- F: +603 8310 6699

Latin America & Caribbean Region

- Ansell Commercial Mexico S.A. de C.V.
Blvd. Bernardo Quintana No. 7001-C,
Q7001 Torre II.
Suites 1304, 1305 y 1306.
Col. Centro Sur, c.p. 76079
Queretaro, Qro. Mexico
- T: +52 442 248 1544 / 248 3133

Canada

- Ansell Canada
105 Lauder
Owensville, QC J2K 2K8
Canada
- T: +1 800 363 8340
- F: +1 800 267 3551

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2020 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

□