



by Honeywell

---

## Technical Specifications

### Titan restraint lanyard

#### References:

- 1008270: Rope restraint lanyard 12 mm, 1 m without connector
- 1008271: Rope restraint lanyard 12 mm, 1.5m without connector
- 1008272: Rope restraint lanyard 12 mm, 2m without connector
- 1008273: Adjustable restraint lanyard in rope 14mm, 1.8m without connector

#### Features:

##### Rope:

Raw material: Polyamide

Width: 12mm (ref: 1008270-71-72), 14mm (ref 1008273)

Breaking strength: >2900daN

Breaking strength :> 15KN

##### Weight:

1008270: 0.150Kg

1008271:0.190Kg

1008272: 0.275Kg

1008273: 0.335Kg

EN354



#### **LAW of 19 MARCH 93**

PPE are products classified in category III, mortal risks, and as such they have to be the object of a periodic inspection for less than twelve months at the time of its use by the qualified person.

For more information, please contact our technical team at 02 48 52 40 42 or by e-mail [techniserv.hsp@honeywell.com](mailto:techniserv.hsp@honeywell.com)

---

HONEYWELL FALL PROTECTION FRANCE SAS

35-37 rue de la Bidauderie

F - 18100 Vierzon - France

Tel : +33 2 48 52 40 40

Fax : +33 2 48 71 04 97

Web site : [www.honeywellsafety.com](http://www.honeywellsafety.com)